

Features:

- High efficiency
- Low power consumption
- General purpose leads
- Selected minimum intensities
- Available on tape and reel

Descriptions:

- The series is specially designed for applications requiring higher brightness.
- The LED lamps are available with different colors, intensities, epoxy colors etc...
- Superior performance in outdoor environment.


Usage Notes:

- The ultra bright LED is an electrostatic device, so static electricity and surge will damage the LED. It is required to wear a wrist-band when handling the LED. All device, equipment, machinery, desk and ground must be properly grounded.
- When using LED, it must use a protective resistor in series with DC current about 20mA.

Applications:

- Status indicators
- Commercial use
- Advertising signs
- Back lighting

Package Dimensions (Units: mm)



Notes:

- Other dimensions are in millimeters, tolerance is 0.25mm except where specified.
- Protruted resin under flange is 1.5mm Max. LED.
- Bare copper alloy is exposed at tie-bar portion after cutting.

Led Part No.	Chip		Lens Color
	Material	Emitted Color	
5-22-WC30-KB	InGaN	White	Water Clear

Absolute Maximum Rating (Ta = 25°C)

Parameter	Symbol	Absolute Maximum Rating	Unit
Forward Pulse Current	I_{FPM}	70	mA
Forward Current	I_{FM}	30	mA
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	140	mW
Operating Temperature	Topr	-40 to +80	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Heat (5s)	Tsol	260	°C


Electro-Optical Characteristics (Ta = 25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	I_V	12000	16000	18000	mcd	IF = 20mA (Note 1)
Viewing Angle	$2\theta_{1/2}$	10	15	20	Deg	(Note 2)
Peak Emission Wavelength	λ_p	-	-	-	nm	IF = 20mA
Spectral Line Half-Width	$\Delta\lambda$	25	30	35	nm	IF = 20mA
Forward Voltage	V_F	2.9	-	3.5	V	IF = 20mA
Reverse Current	I_R	-	-	10	μA	VR = 5V


Notes:

- Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
- $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.



Typical Electro-Optical Characteristics Curves




Forward Current VS. Forward Voltage




Forward Current VS. Relative Intensity



Forward Current VS. Ambient Temp.



Radiation Characteristics



Notes:

1. Above specification may be changed without notice. Ever-led will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. Ever-Led assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.