

Housing: Die-Cast Aluminum, Painted Black
 Blade: Thermoplastic UL 94V-0 P.B.T.
 Insulation Resistance: 100M Ω , 500VDC/min between bare wire and frame
 Dielectric Strength: 1500VAC for one minute
 Operation Temperature: -10°C-70°C(Humidity 35%-85%RH)
 Storage Temperature: -40°C-85°C(Humidity 35%-85%RH)
 Motor Protection: Thermal Protected
 Weight: 520 g

AC AXIAL FAN
127x127x38mm



SS IP

| Model Number | Voltage VAC | Frequency Hz | AirFlow CFM | Stat.Pres. mm-H ₂ O | Noise dBA | Speed RPM | Current mA | Power W | Avail Bearing | Curves |
|-----------------|-------------|--------------|-------------|--------------------------------|-----------|-------------|------------|---------|---------------|--------|
| FA1273B11T7C-31 | 115 | 50/60 | 118.8/139.1 | 7.2/8.7 | 41.4/45.3 | 2,500/2,900 | 160/160 | 20/20 | B,5 | ①/② |
| FA1273B11T9C-31 | 115 | 50/60 | 134.0/153.3 | 10.5/13.2 | 44.3/48.3 | 2,800/3,300 | 210/210 | 25/25 | B,5 | ③/④ |
| FA1273B22T7C-31 | 230 | 50/60 | 118.8/139.1 | 7.2/8.7 | 41.4/45.3 | 2,500/2,900 | 90/90 | 20/20 | B,5 | ①/② |
| FA1273B22T9C-31 | 230 | 50/60 | 134.0/153.3 | 10.5/13.2 | 44.3/48.3 | 2,800/3,300 | 120/120 | 25/25 | B,5 | ③/④ |

- For "Sleeve" bearing version, change the "B" in the model number to "S".
- For "Wire Lead" version, change the "T" in the model number to "W".

Specification are subject to change without notice

