



Housing: Die-Cast Aluminum, Painted Black
 Blade: Thermoplastic UL 94V-0 P.B.T.
 Insulation Resistance: 100M Ω , 500VDC/min between bare wire and frame
 Dielectric Strength: 1500VAC for one minute
 Operation Temperature: -20°C-70°C(Humidity 35%-85%RH)
 Storage Temperature: -40°C-85°C(Humidity 35%-85%RH)
 Motor Protection: Thermal Protected
 Weight: 710 g

AC AXIAL FAN
172x150x38mm



SS IP

Model Number	Voltage VAC	Frequency Hz	AirFlow CFM	Stat.Pres. mm-H ₂ O	Noise dBA	Speed RPM	Current mA	Power W	Avail Bearing	Curves
FA1738B11T7C-32	115	50/60	168.5/201.0	17.0/19.8	56.1/60.1	2,850/3,400	250/260	30/31	B, S	①/②
FA1738B22T7C-32	230	50/60	168.5/201.0	17.0/19.8	56.1/60.1	2,850/3,400	160/170	36/35	B, S	①/②

- For "Sleeve" bearing version, change the "B" in the model number to "S".
 - For "Wire Lead" version, change the "T" in the model number to "W".
- Specification are subject to change without notice

