



Housing: Die-Cast Aluminum, Painted Black
 Blade: Thermoplastic UL 94V-0 P.B.T.
 Insulation Resistance: 100MΩ, 500VDC/min between bare wire and frame
 Dielectric Strength: 1500VAC for one minute
 Operation Temperature: -10°C-70°C(Humidity 35%-85%RH)
 Storage Temperature: -40°C-85°C(Humidity 35%-85%RH)
 Motor Protection: Impedance Protected
 Weight: 340 g

AC AXIAL FAN
80x80x38mm



SS IP

Model Number	Voltage VAC	Frequency Hz	AirFlow CFM	Stat.Pres. mm-H ₂ O	Noise dBA	Speed RPM	Current mA	Power W	Avail Bearing	Curves
FA8038B11T5-61	115	50/60	22.3/26.4	2.8/4.6	25.6/29.6	2,300/2,700	100/100	9/7	B, S	①/②
FA8038B11T7-61	115	50/60	26.4/29.4	3.8/5.1	27.6/33.5	2,700/3,000	200/200	16/12	B, S	③/④
FA8038B22T5-61	230	50/60	22.3/26.4	2.8/4.6	25.6/29.6	2,300/2,700	60/60	7/6	B, S	①/②
FA8038B22T7-61	230	50/60	26.4/29.4	3.8/5.1	27.6/33.5	2,700/3,000	80/80	14/10	B, S	③/④

- For Wire lead version, change "T" in the model number to "W".
- For Sleeve Bearing version, change "B" in the model number to "S".

Specification are subject to change without notice

