



Construction: Ceramic Tube
 Rated current: 0.05A-30A
 Approvals: UL, CSA
 From 0.1-15A 125V, 0.1-10A
 125V/250V

Electrical Characteristic

Rated Current	1 In	2 In
	Min.	Max.
50mA-30A	4 h	60 sec



FAC360 Series
Fast Acting, Ceramic Tube

Part Number	Rated Current	Breaking Capacity	Rated Voltage
FAC360-0.050-__	50mA		
FAC360-0.060-__	60mA		
FAC360-0.063-__	1/16A		
FAC360-0.070-__	70mA		
FAC360-0.080-__	80mA		
FAC360-0.100-__	100Ma		
FAC360-0.125-__	125mA		
FAC360-0.160-__	160mA		
FAC360-0.200-__	200mA		
FAC360-0.250-__	250mA		
FAC360-0.300-__	300mA		
FAC360-0.315-__	315mA		
FAC360-0.400-__	400mA		
FAC360-0.500-__	500mA		
FAC360-0.600-__	600mA		
FAC360-0.630-__	630mA		
FAC360-0.700-__	700mA		
FAC360-0.800-__	800mA		
FAC360-001-__	1A		
FAC360-1.25-__	1.25A	50A @ 125V/AC	
FAC360-1.50-__	1.5A		125V/250V
FAC360-1.60-__	1.6A	50A @ 250V/AC	
FAC360-002-__	2A		
FAC360-2.50-__	2.5A		
FAC360-003-__	3A		
FAC360-3.15-__	3.15A		
FAC360-3.50-__	3.5A		
FAC360-004-__	4A		
FAC360-005-__	5A		
FAC360-006-__	6A		
FAC360-6.30-__	6.3A		
FAC360-007-__	7A		
FAC360-008-__	8A		
FAC360-010-__	10A		
FAC360-012-__	12A		
FAC360-013-__	13A		
FAC360-015-__	15A		
FAC360-016-__	16A		
FAC360-020-__	20A		
FAC360-025-__	25A		
FAC360-030-__	30A		

└─ Style Options: Nil = Axial w/o Leads
P = Radial Straight Leads
PA = Axial with Leads
PR = Radial Bent Leads
ex. FAC360-3.15-PR

PR = Radial Bent Leads

ex. FAC360-3.15-PR