



Construction:Glass Tube

Rated current:0.1A-30A

Rated Voltage:125V/250V

Standard:UL248,CSA C22.2 248

Electrical Characteristic

Rated Current	1 In	2 In
In	Min.	Max.
0.1A-30A	4 h	60 sec



FAG360 Series
Fast Acting, Glass Tube

Part Number	Rated Current	Breaking Capacity	Rated Voltage
FAG360-0.100-__	100mA	50A @ 125V/AC 50A @ 250V/AC	125V/250V
FAG360-0.125-__	125mA		
FAG360-0.160-__	160mA		
FAG360-0.200-__	200mA		
FAG360-0.250-__	250mA		
FAG360-0.300-__	300mA		
FAG360-0.315-__	315mA		
FAG360-0.400-__	400mA		
FAG360-0.500-__	500mA		
FAG360-0.600-__	600mA		
FAG360-0.630-__	630mA		
FAG360-0.700-__	700mA		
FAG360-0.800-__	800mA		
FAG360-001-__	1A		
FAG360-1.25-__	1.25A		
FAG360-1.50-__	1.5A		
FAG360-1.60-__	1.6A		
FAG360-002-__	2A		
FAG360-2.50-__	2.5A		
FAG360-003-__	3A		
FAG360-3.15-__	3.15A		
FAG360-3.50-__	3.5A		
FAG360-004-__	4A		
FAG360-005-__	5A		
FAG360-006-__	6A		
FAG360-6.30-__	6.3A		
FAG360-007-__	7A		
FAG360-008-__	8A		
FAG360-010-__	10A		
FAG360-012-__	12A		
FAG360-013-__	13A		
FAG360-015-__	15A		
FAG360-016-__	16A		
FAG360-020-__	20A		
FAG360-025-__	25A		
FAG360-030-__	30A		

_____ Style Options: Nil = Axial w/o Leads
 P = Radial Straight Leads
 PA = Axial with Leads
 PR = Radial Bent Leads
ex. FAG360-3.15-PR