



Construction: Glass Tube
 Rated current : 0.1A-30A
 Rated Voltage: 32V/125V/250V
 Standard: UL, CSA

Electrical Characteristic

Rated Current	1 In	1.35 In	2 In
In	Min.	Max.	Max.
0.1A-30A	4 h	3600 S	120 S



FAG635-25 Series
Slow Blow, Ceramic Tube

Part Number	Rated Current	Breaking Capacity	Rated Voltage
FAG635-25-0.100-__	100mA	35A @ 250V/AC 10KA @ 125V/AC	125V/250V
FAG635-25-0.125-__	125mA		
FAG635-25-0.160-__	188mA		
FAG635-25-0.200-__	200mA		
FAG635-25-0.250-__	250mA		
FAG635-25-0.300-__	300mA		
FAG635-25-0.315-__	375mA		
FAG635-25-0.400-__	400mA		
FAG635-25-0.500-__	500mA		
FAG635-25-0.600-__	750mA		
FAG635-25-001-__	1A		
FAG635-25-1.25-__	1.25A		
FAG635-25-1.50-__	1.5A		
FAG635-25-002-__	2A		
FAG635-25-2.50-__	2.5A	1000A @ 32V/AC	32V
FAG635-25-003-__	3A		
FAG635-25-3.15-__	4A		
FAG635-25-3.50-__	5A		
FAG635-25-004-__	6A		
FAG635-25-005-__	7A		
FAG635-25-006-__	8A		
FAG635-25-6.30-__	10A		
FAG635-25-007-__	15A		
FAG635-25-008-__	20A		
FAG635-25-010-__	25A		
FAG635-25-012-__	30A		