



Constructiion: Ceramic Tube
 Rated current: 0.05A-30A
 Rated Voltage: 125V/250V
 Approvals: JIS C6575, 15A and less

Electrical Characteristic

Rated Current	1.3 In	1.6 In	2 In
In	Min.	Max.	Max.
50mA-30A	4 h	60 min	120 S



NBC635 Series
Normal Blow, Ceramic Tube

Part Number	Rated Current	Breaking Capacity	Rated Voltage
NBC635-0.030-__	30mA	35A @ 250V/AC 10KA @ 250V/AC	125V/250V
NBC635-0.060-__	60mA		
NBC635-0.063-__	1/16A		
NBC635-0.070-__	70mA		
NBC635-0.080-__	80mA		
NBC635-0.100-__	100Ma		
NBC635-0.125-__	125mA		
NBC635-0.160-__	160mA		
NBC635-0.200-__	200mA		
NBC635-0.250-__	250mA		
NBC635-0.300-__	300mA		
NBC635-0.315-__	315mA		
NBC635-0.400-__	400mA		
NBC635-0.500-__	500mA		
NBC635-0.600-__	600mA		
NBC635-0.630-__	630mA		
NBC635-0.700-__	700mA		
NBC635-0.800-__	800mA		
NBC635-001-__	1A		
NBC635-1.25-__	1.25A		
NBC635-1.50-__	1.5A		
NBC635-1.60-__	1.6A		
NBC635-002-__	2A		
NBC635-2.50-__	2.5A		
NBC635-003-__	3A		
NBC635-3.15-__	3.15A		
NBC635-3.50-__	3.5A		
NBC635-004-__	4A		
NBC635-005-__	5A		
NBC635-006-__	6A	200A @ 250V/AC 10KA @ 125V/AC	
NBC635-6.30-__	6.3A		
NBC635-007-__	7A		
NBC635-008-__	8A		
NBC635-010-__	10A		
NBC635-012-__	12A		
NBC635-013-__	13A	1000A @ 125V/AC	125V
NBC635-015-__	15A		
NBC635-016-__	16A		
NBC635-020-__	20A	1000A @ 32V/AC/DC	32V
NBC635-025-__	25A		
NBC635-030-__	30A		
NBC635-030-__	30A		

└─ Style Options: Nil = Axial w/o Leads
 P = Radial Straight Leads
 PA = Axial with Leads
 PR = Radial Bent Leads
 ex. NBC635-3.15-PR