


RSL SERIES

Low Leakage, Subminiature, Radial Leads

■ Features

- Subminiature Low leakage current, Radial
- Lengths are all 7mm
- Ideal for tantalum capacitor replacement
- Load life of 1000 hours at 85°C




■ Specifications

Item	Performance Characteristics						
Operating temperature range	-40°C ~ +85°C						
Rated working voltage range	6.3V ~ 50V						
Nominal capacitance range	0.1μF ~ 100μF, ±20% (at 20°C, 120Hz)						
D.C Leakage current(at 20°C)	The following specifications shall be satisfied when the rated voltage is applied for the required time. $I \leq 0.002CV$ or $0.4\mu A$ (2 min), whichever is greater Where I =Leakage current(μA) C=Nominal capacitance(μF) V=Rated voltage(V)						
Tan δ (max., at 20°C, 120Hz)	W.V(V)	6.3	10	16	25	35	50
	Tan δ	0.24	0.20	0.17	0.15	0.12	0.10
Characteristics at low temperature(max.) (impedance ratio at 120Hz)	W.V(V)	6.3	10	16	25	35	50
	Z-25°C/Z20°C	4	3	2	2	2	2
	Z-40°C/Z20°C	8	6	4	4	4	4
Load life	After applying rated working voltage for 1000 hours at +85°C and then being stabilized at +20°C, capacitors shall meet following limits.						
	Capacitance change	Within ± 25% of the initial measured value					
	Tan δ	≤ 150% of the initial specified value					
	Leakage current	≤ The initial specified value					
Shelf life	After storage for 1000 hours at +85°C with no voltage applied and then being stabilized at +20°C, capacitors shall meet following limits.						
	Capacitance change	Within ± 20% of the initial measured value					
	Tan δ	≤ 150% of the initial specified value					
	Leakage current	≤ 200% of the initial specified value					

Low LC

■ Dimensions



- Standard lead style

φD	4.0	5.0	6.3
P	1.5	2.0	2.5
φd	0.45		

D' = [D+0.5]Max.

L' = [L+1.0]Max.

■ Dimensions & Maximum permissible ripple current

W.V(V) Cap(μF)	φD x L(mm)											
	6.3(0J)		10(1A)		16(1C)		25(1E)		35(1V)		50(1H)	
	SIZE	I _r	SIZE	I _r	SIZE	I _r	SIZE	I _r	SIZE	I _r	SIZE	I _r
0.1											4x7	2
0.22											4x7	4
0.33											4x7	6
0.47											4x7	8
1.0											4x7	11
2.2											4x7	20
3.3											4x7	27
4.7							4x7	25	4x7	27	5x7	35
6.8					4x7	30	5x7	30	5x7	35	6.3x7	40
10					4x7	40	5x7	47	5x7	47	6.3x7	52
22	4x7	37	5x7	46	5x7	47	6.3x7	62	6.3x7	62		
33	5x7	52	5x7	55	6.3x7	72	6.3x7	92				
47	5x7	65	6.3x7	82	6.3x7	82						
100	6.3x7	92										

I_r: Maximum permissible ripple current[mA(rms) at 85°C, 120Hz]


ORDERING INFORMATION for Leaded Type



Daewoo Components Corp.

Through-Hole Part Numbering System Example:

RM = Leaded Radial 85°C Miniature Series, **102** = 1000µF, **M** =20% Tolerance, **1E** 25 Volts, **B** = Bulk,
1020 = Case size (Dia x H) = 10.0 x 20.0mm, **E** = 5.0mm



(1) Series

See Quick Guide on page 2
Example: RSS, RM, RMU,...

(2) Capacitance Value Code

Capacitance expressed in micro Farads (µF)
First two digits are significant figures
Third digit denotes the number of zeros
Use R for decimal point for values less than 10µF

Examples:

CODE	Capacitance
R10	0.1 µF
R68	0.68 µF
1R0	1.0 µF
100	10 µF
680	68 µF
471	470 µF
102	1000 µF
103	10000 µF

(3) Capacitance Tolerance Code

CODE	Cap. Tol.	CODE	Cap. Tol.
J	±5%	V	-10% ~ +20%
K	±10%	Q	-10% ~ +30%
M	±20%	T	-10% ~ +50%
R	+20%, -0%		

(4) Rated Voltage Code

CODE	Voltage	CODE	Voltage
0G	4.0V	2C	160V
0J	6.3V	2S	180V
1A	10V	2D	200V
1C	16V	2E	250V
1E	25V	2F	315V
1V	35V	2V	350V
1H	50V	2G	400V
1J	63V	2W	450V
1K	80V	3Z	1000V
2A	100V		

(5) Packaging Form & Lead Style Code (see page 7, 8, 9 for details)

	Code	Packaging Form & Lead Style
Bulk	B	Bulk: Standard Package
	L	Bulk: 4 -8ø Long Leads Formed to 5 mm Pitch
Snap-In	1	10-13ø Snap-in Cut 5.0mm
	2	16-13ø Snap-in Cut 5.0mm
	3	10-13ø Snap-in Cut 4.5mm
	4	16-18ø Snap-in Cut 4.5mm
	5	4-8ø Snap-in Cut 7.5mm
Form	F	4-8ø Forming Cut 6.5mm
	G	4-8ø Forming Cut 10.0mm
Straight Cut	C	4-18ø Straight Cut 4.0mm
	6	4-18ø Straight Cut 3.1mm
	7	4-18ø Straight Cut 5.0mm
	8	4-18ø Straight Cut 6.35mm
Ammo Tape (+) Leading	A	4-8ø Straight Ammo Detail Ranges: 4-6.3ø; F=2.5mm 8ø; F=3.5mm
		4-8ø Form Tape & Ammo 5mm Pitch
		10ø Straight Ammo Tape 5mm Pitch
		13ø Straight Ammo Tape 5mm Pitch
		16-18ø Straight Ammo Tape 5mm Pitch
Tape & Reel (+) Leading	T	4-8ø Straight Ammo Detail Ranges: 4-6.3ø; F=2.5mm 8ø; F=3.5mm
		4-13ø Form Tape & Reel 5mm Pitch
		10-13ø Straight Reel Tape 5mm Pitch

NOTE: Standard Pack Anode(+) Lead Leading FEEDS OFF FIRST
Special Option Cathode(-) Lead Leading available upon request
Standard Packages: B = Bulk, A = Ammo, T = Tape & Reel

(6) Example Dimension Code (Diameter x Height in mm)

Size Code	Diameter	Height	Size Code	Diameter	Height
0405	4	5	1320	13	20
0407	4	7	1631	16	31.5
0505	5	5	1835	18	35.5
0507	5	7	2240	22	40
0607	6.3	7	2545	25	45
0511	5	11	3035	30	35
0605	6	5	3500	35	100
0611	6.3	11	3501	35	110
0805	8	5	5102	51	120
0811	8	11	6303	63.5	130
1012	10	12.5	7604	76	140
1220	12.5	20	8904	89	140

(7) Lead Spacing Code (LS)

Code	X	A	B	C	D	E	J	F
LS	1.0	1.5	2.0	2.5	3.5	5.0	7.0	7.5
Code	K	M	G	P	H	Q	R	S
LS	8.0	10.0	10.5	12.0	12.5	12.8	15.0	16.0
Code	T	U	V	W	Y	Z		
LS	20.0	21.7	28.3	30.0	31.6	32		