

**HOOK-UP WIRE**  
**SEMI RIGID PVC INSULATION**  
 UL 1061, CSA I A/B FT1  
 RoHS COMPLIANT  
 300 VOLT



**CHARACTERISTICS**

**Operating Temperature:**

-10°C to 80°C

**Voltage Rating:**

300 Volt

**Product Description:**

Conductor: Stranded or Solid Tinned Copper  
 Insulation : Color-Coded, Semi Rigid PVC



**STRAND CONDUCTOR**

Series	Conductor		Insul. Thickness		Diameter		Stock Colors*
	AWG	Strand	Inches	mm	Inches	mm	
SRPVC 24-7	24	7/32	0.009	0.23	0.042	1.07	1-10
SRPVC 22-7	22	7/30	0.009	0.23	0.048	1.22	1-10
SRPVC 20-7	20	7/28	0.009	0.23	0.056	1.42	1-10
SRPVC 18-7	18	7/26	0.009	0.23	0.066	1.68	1-10
SRPVC 16-7	16	7/24	0.009	0.23	0.078	1.98	1-10

\*See Color Code Below

**SPECIFICATIONS**

UL AWM Styles 1061  
 CSA AWM I A/B FT1  
 RoHS Compliant


**AVAILABILITY**

100 ft (30.5m), 1000ft(305m) put-ups

*STOCK COLOR CHART							
1-White	4-Green	7-Brown	10-Violet (purple)	13-White/ Green	16-White/ Brown	19-White/ Violet	30-Pink
2-Black	5-Yellow	8-Orange	11-White/ Black	14-White/ Yellow	17-White/ Orange	28-Green/ Yellow	
3-Red	6-Blue	9-Gray	12-White/ Red	15-White/ Blue	18-White/ Gray	29-Yellow/ Green	



**PART NUMBERING SYSTEM**



- Color Code:
- WHT = White
  - BLK = Black
  - RED = Red
  - GRN = Green
  - YEL = Yellow
  - BLU = Blue
  - BRN = Brown
  - ORG = Orange
  - GRY = Gray
  - VIO = Violet
  - WHT/BLK = White/Black
  - WHT/RED = White/Red
  - WHT/GRN = White/Green
  - WHT/YEL = White/Yellow
  - WHT/BLU = White/Blue
  - WHT/BRN = White/Brown
  - WHT/ORG = White/Orange
  - WHT/GRY = White/Grey
  - WHT/VIO = White/Violet
  - GRN/YEL = Green/Yellow
  - YEL/GRN = Yellow/Green
  - PNK = Pink