

6. SC-59 TRANSISTORS

(Package): SC-59



Pinout: 1-Emitter, 2-Base, 3-Collector

TYPE	V _{CB0} V	V _{CE0} V	I _c mA	P _D mW	h _{FE}		V _{CE(sat)}		f _T TYP MHz	STYLE
					Min/Max	I _c /V _{CE} mA/Volts	Max Volts	I _c /I _B mA		
MSA1022-BT ₁	-30	-20	-30	200	70/140	-1/-10			150	1
MSA1022-CT ₁	-30	-20	-30	200	110/220	-1/-10			150	1
MSB709-RT ₁	-25	-25	-100	200	210/340	-2.0/-10	-0.5	-100/-10		1
MSB709-ST ₁	-25	-25	-100	200	290/460	-2.0/-10	-0.5	-100/-10		1
MSB710-QT ₁	-30	-25	-500	200	85/170	-150/-10	-0.6	-300/-30		1
MSB710-RT ₁	-30	-25	-500	200	120/240	-150/-10	-0.6	-300/-30		1
MSC1621T ₁	40	20	200	200	40/180	1/0.5	0.25	10/1.0	200	1
MSC2295-BT ₁	30	20	30	200	70/140	I _E /V _{CB} -1/10			150	1
MSC2295-CT ₁	30	20	30	200	110/220	I _E /V _{CB} -1/10				1
MSC2404-CT ₁	30	20	15	150	65/160	I _E /V _{CB} -1/6			450	1
MSC3130T ₁	15	10	50	200	75/400	5/4	0.5	20/4	2.5GHz	1
MSD601-RT ₁	30	25	100	200	210/340	2.0/10	0.5	100/10		1
MSD601-ST ₁	30	25	100	200	290/460	2.0/10	0.5	100/10		1
MSD602-RT ₁	30	25	500	200	120/240	150/10	0.6	300/30		1
MSD1328-RT ₁	25	20	500	200	200/350	500/2	0.4	500/20		1